

VT DBH24K Dome Housing

*Weatherproof your AXIS 213/214/215 PTZ
and AXIS 231D+/232D+/233D
Network Dome Cameras*

VT DBH24K Dome Housing protects the AXIS 213/214/215 PTZ Network Camera and AXIS 231D+/232D+/233D Network Dome Cameras in outdoor environments, as well as in indoor conditions that may be humid, cold or dusty.

The housing provides IP65-class protection from dust and water. With fan-assisted heating, the housing enables the camera to operate in temperatures down to -20°C (-4°F).

Designed to look like a traditional lighting system, the housing allows for discreet surveillance. Its lower semi-sphere covering comes in clear or semitransparent black acrylic glass (PMMA). The housing provides an internal protective passage for cables and is easy to install on ceilings and walls.



- Indoor and outdoor installation
- Operating temperature
 - AXIS 213 PTZ Network Camera:
 -20°C to 30°C (-4°F to 86°F)
 - AXIS 214/215 PTZ Network Camera:
 -20°C to 40°C (-4°F to 104°F)
 - AXIS 231D+/232D+ Network Dome Cameras:
 -20°C to 50°C (-4°F to 122°F)
 - AXIS 233D Network Dome Camera:
 -20°C to 45°C (-4°F to 113°F)
- IP65-class protection from dust and water
- Fan-assisted heater
- A variety of mounting brackets available



DBH24K DOME HOUSING

General

- Made in plastic material. Color: Black (nylon with mineral additives)
- Lower semi-sphere in PMMA. Color: semitransparent black or transparent
- Sunshield in ABS material. Color: RAL9002

Electrical

- For AXIS 213/214/215 PTZ Network Camera, 230 V AC, consumption 44 W
- For AXIS 231D+/232D+/233D Network Dome Camera, using an external power supply, AXIS PS24 (5000-001):
- Input 100-120VAC/220-240VAC; 50-60Hz;89VA
- Output: 24VAC 63VA

Environment

- Indoor or outdoor
- IP65 rated
- Operating temperature
 - AXIS 213 PTZ Network Camera: -20 °C to 30 °C (-4 °F to 86 °F)
 - AXIS 214/215 PTZ Network Camera: -20 °C to 40 °C (-4 °F to 104 °F)
 - AXIS 231D+/232D+ Network Dome Cameras: -20 °C to 50 °C (-4 °F to 122 °F)
 - AXIS 233D Network Dome Camera: -20 °C to 45 °C (-4 °F to 113 °F)
- Fan-assisted heater
 - T on: 15 °C+/-3 °C (59 °F)
 - T off: 22 °C +/-3 °C (71 °F)

Dimensions and Weight

- Height, total: 325 mm (12.79")
- Height, body: 213 mm (8.4")
- Diameter, total: 326 mm (12.83") (with sunshield)
- Diameter, bubble: 231mm (9.1")
- Weight: 2.45 kg (5.4 lb.)

Approvals

- IP65: EN60529
- CE: EN50081-1, EN50082-1

Available accessories

- OPLEX24T Spare bubble, smoked
- OPLEX24F Spare bubble, clear

DBH24K dome housing - accessories and order guide

To receive a fully working unit for outdoor use, please use the following guide and select one item from each column. Items in grey boxes are optional.

1	2	3	4
DBH24K Dome Housing, transparent, 0216-001 	Mounting adapter for AXIS 213 PTZ, 0216-021 	ODBH04 Wall mount, Length: 356 mm (14") Weight: 2.2 kg (4.8 lb.) 0216-041 	DPTCH Pole mount Pole diameters: 80 -150 mm (3.1" - 5.9") Weight: 2.5 kg (5.6 lb.) 0216-061 
	Mounting adapter for AXIS 214 PTZ, 0216-111 	ODBH03 Ceiling mount, Length: 922 mm (36") Weight: 2 kg (4.4 lb.), 0216-031 	DCWGH Corner mount Weight: 2.2 kg (4.8 lb.) 0261-071 
DBH24K Dome Housing, smoked, 0216-011 	Mounting adapter for AXIS 215 PTZ, 0216-121 	ODBH05 Parapet mount, Height: 812 mm (32") Width: 451 mm (17.8") Weight: 5 kg (11 lb), 0216-051 	OHEGB Waterproof junction box (Only for AXIS 213 PTZ Network Camera), 0217-121 
	Mounting adapter for AXIS 231D+/232D+ 0216-101 	Mounting adapter for AXIS 233D, 0216-131 	PS-24 mains power adapter (for AXIS 231D+/232D+/233D Network Dome Cameras), 5000-001 

www.axis.com

©2007 Axis Communications AB. AXIS COMMUNICATIONS, AXIS, ETRAX, ARTPEC and VAPIX are registered trademarks or trademark applications of Axis AB in various legislations. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to introduce modifications without notice.

Channel Partners **Kwikk Soft Solutions Pvt Ltd**, Chennai, India.

